

## Seat Belts for Forklift

Seat Belt for Forklift - Explained in the Regulation guidelines are the application of operative restraints and seatbelts on lift trucks. It states that the responsibility falls on the employers' to be able to make certain that every machine, piece of equipment and tool is used correctly utilized according to the instructions of the maker.

Rough Terrain forklifts must meet the regulations of ANSI Standard ASME B56.6-1992 in regards to their use, design, maintenance, inspection and fabrication.

Mobile machines like side boom tractors with a Rollover Protective Structure (ROPS), should contain seat belts that meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile machine includes seat belts required by law, the operator and subsequent passengers need to make certain they utilize the belts whenever the motor vehicle is in motion or engaged in operation as this can cause the machine to become unsteady and hence, not safe.

If a seat belt or various driver restraint is needed on a lift truck.

The seat belt requirements while operating a lift truck depend on different factors. Whether the forklift is outfitted with a Rollover Protective Structure, the type of forklift itself and the year the forklift was actually manufactured all contribute to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, system or enclosure, ANSI Standard ASME B56.1-1993 with regards to powered industrial trucks, is intended to be able to aid the driver in lessening the chance of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device may comprise a seat belt, while a seat belt is not necessarily a part of such equipment or system.